Unger Enterprises, Inc.

425 Asylum St. Bridgeport, CT 06610

MATERIAL SAFETY DATA SHEET

Revision Date: 8/24/2007

MSDS No. F1023

Emergency Phones: 203-366-4884

PLEASE NOTE: This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL and STATE RIGHT-TO-KNOW regulations. Also make this information available to any employee who requests it. It is your obligation to comply with these regulations.

SECTION I - PRODUCT IDENTITY

PRODUCT NAME: Professional Easy Glide Glass Cleaner

Formula: Mixture, additives and alcohol in water. Chemical Type: As above

HMIS RATINGS	
Health =1 (Slight)	Flammability = 1 (Slight)
Reactivity = 0 (Minimal)	Protection = B (Goggles & Gloves)

SECTION II - HAZARDOUS INGREDIENTS				
Isopropanol (CAS 67-63-0)	<u>PERCENT</u> 0-3%	<u>TLV</u> 400 ppm	CARCINOGEN (OSHA,TP,IARC) No	
Amine Oxide (CAS 61788-90-7)	5-10%	N/A	No	
Ethoxylated Alcohol (CAS 68131-39-5)	0-5%	N/A	No	

Appearance: Clear Green Liquid	Boiling Point: <212°F.	
Odor: Pleasant	Melting Point: N/A	
pH: 9.5-10.5	Spec. Gravity (H ₂ 0 = 1): 0.99	
Water Solubility: Complete	Vapor Pressure (mm Hg): N/A	
Viscosity: Water Thin	VOC Content: 1%	

Flash Point (Method): > 150 °F. Cl.Cp.

Explosion Limits:

Upper: N/A Lower: N/A

Extinguishing Media: Water fog, foam, alcohol foam, CO₂, dry chemical Special Firefighting Procedures and Hazards: Treat as a combustible liquid. **NOTE**: This product is Combustible under OSHA criteria, but is not regulated by DOT since it contains less than 24% alcohol and over 50% water, and the other ingredients do not constitute a DOT hazard: see (CFR173.115(b)(2)(i) and (ii).

SECTION V - REACTIVITY INFORMATION

Unstable:

Stable: 🛛

Precautions: Incompatibility: None known

Hazardous Decomposition Products: If in a fire: CO, CO₂, hydrocarbons.

Hazardous Polymerization: Occurs:

Does Not Occur:

SECTION VI - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Inhalation: Breathing of vapors may cause dizziness and shortness of breath. Wear approved vapor respirator if needed. Remove to fresh air. Skin: Extended contact may cause irritation or defatting. Wear protective gloves if needed. Remove contaminated clothing & wash if necessary before reuse. Flush skin thoroughly with water for 15 minutes. Can cause irritation. Wear goggles as needed. Flush immediately with water for 15 minutes. Get prompt medical attention if Eyes: needed. May cause a mild gastric disturbance. Drink lots of water. Do not induce vomiting. Get medical attention if effects persist.

Ingestion:

Most likely routes of entry: Skin, Eyes.

Other Important Medical or Precautionary Information: None

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills and Leaks: Small spills can be flushed into normal drainage or into ground with copious amounts of water, or taken up with absorbent material. Larger spills should be contained by diking or other methods and held for disposal or reuse. Remove all sources of ignition. Provide strong ventilation.

Storage and Handling: Check daily for any leaks from containers, vessels, pumps, and piping. Keep away from sources of ignition. Keep at temperatures below 95oF.

Waste Disposal: Collect in closed containers and send to a licensed treatment or disposal facility.

Empty Containers: Rinse well before handling and disposal. Observe label precautions. Do not cut, weld or burn.

Other Precautions: None

SECTION VIII - REGULATORY INFORMATION

Reportable for SARA Title III, S.313 (Form R): None

The information herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, Unger Enterprises cannot give any guarantees regarding information from other sources, and expressly does not make any warranties, nor assumes any liability, for its use.