

Glide Friction Reducer

Material Safety Data Sheet

Prepared Jan. 2009

Page 1 of 2

Sorbo Products
P.O. Box 1312
Palm Desert, CA. 92281
(780)202-4003 FAX:(760)202-3003
www.sorboproducts.com

TRADE NAME: **Sorbo Glide**

HAZARD CLASSIFICATION LABEL: None

FORMULA:

CHEMICAL NAME: **Nonionic Surfactant**

I HAZARDOUS INGREDIENTS

WEIGHT % TWA/TLV

II PHYSICAL DATA			
Appearance:	Hazy liquid	pH:	
Viscosity @ 100°C:	54.5 cST	Odor:	Some
Boiling Point:	High	Melting or Freezing point:	NA
Vapor Density (Air = 1):	NA	Vapor Pressure (mm Hg):	Low
Percent Volatile (by weight):	Nil	Solubility in Water:	Soluble
Evaporation Rate (Butyl Acetate=1):	Nil		
Specific Gravity:	1.003		

HI - FIRE AND EXPLOSIVE HAZARD DATA			
Flash Point:	450° F	Auto Ignition Temperature:	NA
Lower Explosion Limit (%):	NA	Upper Explosion Limit (%):	NA
Extinguishing Media:	Foam	Alcohol Foam	Co ₂
	Dry Chemical	Water Fog	Other

SPECIAL FIRE FIGHTING PROCEDURES:

Use water to cool fire-exposed containers. If a leak or spill has ignited., use water spray to disperse vapors.

UNUSUAL FIRE AND EXPLOSION HAZARDS : NONE

Glide Friction Reducer

Material Safety Data Sheet

Page 2 of 2

REACTIVITY DATA

Stability:	Stable
Incompatibility:	Strong Mineral Acids
Conditions to Avoid:	Slippery when wet. Moisture causes caking.
Hazardous Polymerization:	Will not occur

SPECIAL PROTECTION

Respiratory Protection:	U.S. Bureau of Mines approved toxic dust mask
Eye Protection:	Chemical type goggles
Ventilation:	No
Protective Equipment:	Full cover non-absorbent clothing. Protective gloves.

SPILL OR LEAK PROCEDURES

For minor spills the material should be swept up and discarded in the general dump.

Residue can be washed away with water.

Waste Disposable Method - Flush to sewer with excessive amount of water.

PRECAUTIONS TO BE TAKEN IN SHIPPING, HANDLING & STORING

Store in dry area. Avoid contact with acids.

Transporting Data - Proper shipping name - Compound, Cleaning - Dry. Non-hazardous material.

No special precautions. Keep dry.