



Triple Crown Gold WaterFed® Pole

Effective November 2024

Getting Started With Your Pole Operation and Maintenance Manual



Overview

Congratulations on your purchase.

Thank you for selecting a Triple Crown Gold WaterFed® Pole. Built with high quality materials and featuring industry leading technology, we are sure that you'll enjoy your new pole. This guide will run you through the basic dos and don'ts of your pole along with instructions for setting it up out of the box.

CAUTION



**DON'T USE
NEAR ELECTRICITY!**

CAUTION



**DO NOT
DROP POLE!**

In The Box

Parts Check

- Triple Crown Gold WaterFed® Pole
- Brush
- Pole Tubing w/ Pole Connector
- Double Plastic Angle Adaptor
- Shut-Off Valve

1. Unpacking/Inspecting The Pole

Carefully remove the packaging material from around your pole and discard. Examine all collars and sections to make sure that nothing was damaged in shipping. If damage has occurred, notify abc Window Cleaning Supply within 48 hours. Some of the hardware on your Triple Crown Gold Pole may have loosened in shipping. Adjust the tension of the clamp using the thumbscrew. Do not over tighten.

2. Initial Setup

You can watch the video at:
www.abcWindowSupply.com/GoldGuide



1. Remove the metal tip by disengaging the 1 Collar.
2. Run the open end of your pole tubing through the bottom of your pole. Feed it through until it is coming out the top.
3. Run the tubing through your metal pole tip.
4. Using a thin tool (a pen works well), feed the tubing through the hole on the side of the tip.
5. Push the metal tip into the 1 Collar. Engage the 1 Collar.
6. Screw your Double Angle Adaptor onto the metal pole tip.
7. Screw brush onto euro threaded side of your Double Angle Adapter. Adjust until it's straight.
8. Attach pole tubing to quick connect on the brush. If your brush has multiple jets, select the fitting for the jets that you want to use.
9. Connect Shut Off Valve to Quick Connect at the end of the pole tubing that is coming from the bottom of the pole.
10. Connect to pure water system of choice and clean windows!

3. Replacement Parts

Edge™ 260 DuPont® Brush - EDGE-260-DUPONT
 Double Angle Adaptor - TCSWITCH
 Tip - 6000-G-TIP
 Collar - 6000-G-RC[x]
 Section - 6001-G-[x]-[x]
 Shut-Off Valve - WF601311
 Tubing - WF600600-[x]

Optional Accessories

5' Extension Section - 6000-G-E-5
 For 25' and longer poles
 Carbon Gooseneck - 6000-G-GN[x]-CF

