

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at [PETZL.COM](https://www.petzl.com).

NON-ADJUSTABLE ROPE LANYARD

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Croles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
---	---	---	---	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

3. Checking the condition of the rope

- Remove the connectors from the lanyard ends. Move the protective sleeve in order to check the covered parts.
- Look for wear and damage on the sheath due to use (cuts, fuzziness, chemical residues...).
- Do a tactile inspection of the core along the full length of the rope (hard spots, swelling, soft or crushed areas...).
- Check the condition of the rope at the harness attachment holes and at the ends of the lanyard.
- Check the condition of the safety stitching on both sides. Look for any threads that are loose, worn, or cut.
- Verify that the fall indicator is present (only on the PROGRESS).

4. Checking the condition of the connectors

- For connector inspection, see the inspection form for your connector model at Petzl.com.

5. Reinstalling the connectors

- Reinstall the connectors. Verify that the plastic protector correctly positions the connector.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product fit to remain in service
Product unfit to remain in service

Inspected by	
Company	
Date	Next inspection date