



Triple Crown Silver WaterFed® Pole

Effective November 2024

Getting Started With Your Pole Operation and Maintenance Manual



Overview

Congratulations on your purchase.

Thank you for selecting a Triple Crown Silver WaterFed® Pole. Built with high quality materials and featuring industry leading technology, we are sure that you'll enjoy your new pole. This guide will run you through the basic dos and don'ts of your pole along with instructions for setting it up out of the box.

CAUTION



**DON'T USE
NEAR ELECTRICITY!**

CAUTION



**DO NOT
DROP POLE!**

In The Box

Parts Check

- Triple Crown Silver WaterFed® Pole
- Brush
- Pole Tubing w/ Pole Connector
- Double Plastic Angle Adaptor
- Shut-Off Valve
- Allen Wrench

1. Unpacking/Inspecting The Pole

Carefully remove the packaging material from around your pole and discard. Examine all collars and sections to make sure that nothing was damaged in shipping. If damage has occurred, notify abc Window Cleaning Supply within 48 hours. Some of the hardware on your Triple Crown Silver Pole may have loosened in shipping. Check that each clamp is firmly attached to its base section using the allen wrench. Then adjust the tension of the clamp using the thumbscrew. Hardware should be tightened enough to keep collars on their section without spinning - do not over tighten.

2. Initial Setup

You can watch the video at:
www.abcWindowSupply.com/SilverGuide



1. Remove the metal tip by disengaging the O Collar.
2. Run the open end of your pole tubing through the bottom of your pole. Feed it through until it is coming out the top.
3. Run the tubing through your metal pole tip.
4. Using a thin tool (a pen works well), feed the tubing through the hole on the side of the tip.
5. Push the metal tip into the O collar. Engage the O collar.
6. Screw your Double Angle Adapter onto the metal pole tip.
7. Screw brush onto euro threaded side of your Double Angle Adapter. Adjust until it's straight.
8. Attach pole tubing to quick connect on the brush. If your brush has multiple jets, select the fitting for the jets that you want to use.
9. Connect Shut Off Valve to Quick Connect at the end of the pole tubing that is coming from the bottom of the pole.
10. Connect to pure water system of choice and clean windows!

3. Replacement Parts

Edge™ 260 DuPont® Brush - EDGE-260-DUPONT

Double Angle Adaptor - TCSWITCH

Tip - 6000-S-1Tip

Collar - 6000-S-RC[x]

Section - 6001-S-[x]

End Cap - 6000-S-EC[x]

Shut-Off Valve - WF601311

Tubing - WF600600-[x]

Optional Accessories

2 Section Extension - 09' - 6000-S-2-09HY

For 35' Hybrid

2 Section Extension - 11' - 6000-S-2-11CF

For 45' HMC

Acme Tip - 6000-S-1-ACME

Carbon Gooseneck - 6000-S-GN[x]-CF

